



Doc# 5482210



WCCS - DANE COUNTY
BEARINGS ARE REFERRED TO THE EAST
BY THE FOLLOWING LINE TO BEAR = N 00°22'12" E

SCALE 1" = 60'

0' 60' 120' 180'

REDTAIL ACKERS SUBDIVISION

A parcel of land located in part of the Southeast 1/4 of the Southwest 1/4 of Section 31, T8N, R9E, City of Middleton, Wisconsin, is hereby subdivided into 14 lots, as shown on the plat. The plat is recorded in the County Register of Deeds, Office in Volume 92 of Certified Surveys on Page 273 through 278, as Document No. 5133990.

WILLIAMSON SURVEYING & ASSOCIATES, LLC

104 N. WEST MAIN STREET, SUITE 200, MADISON, WISCONSIN 53703
PHONE: 608-833-5705 FAX: 608-846-9760 WEB: WILLIAMSONSURVEYING.COM

WILLIAMSON SURVEYING & ASSOCIATES, LLC
NDA T. BRIEVE, & CHRIS V. ADAMS
REGISTERED PROFESSIONAL SURVEYORS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

SETBACKS ARE TO BUILDING CORNERS
AND NOT TO CURB OR RAILROADS.
TYPICAL SETBACKS
UNLESS NOTED

LEGEND
O = SETBACK 1' FROM CURB OR RAILROAD
ALL OTHER LOT AND OUTLOT
CORNERS ARE MARKED WITH
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
5/8" DIA. REBAR, MINIMUM
(H) = NO VEHICULAR ACCESS

NORTH 1/4 CORNER
SECTION 31-8-9
F.D. BRASS MONUMENT

4914.62

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

4914.62

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

4914.62

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

4914.62

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

80°

<